



Miami



Textaafoam
Expect what's next in furniture fabrics

| Comfort



Miami

Meet Miami, a Textaafoam Original. A nice elegant and soft quality with a voluminous grip which is in our Comfort Collection. This collection stands for softness, volume and elegance.

Miami is piece dyed, woven on a dobby loom and has chenille in the weft, it has a composition of 70% polyester and 30% viscose. This creates a nice light shiny and melange aspect. Treated with a special CO/ PFAS free finish, therefor it is easy to clean and maintain only with a damp cloth.

Chenille fabrics, such as Miami, are perfect for creating cozy, warm and elegant furniture. Kindly note that during use a sitting mirror/ seat depression will appear, this can be minimized by brushing Miami on a regular base. Important is to mention that this can never be taken away completely.

Sitting mirror and shading are properties of this type of chenille textiles, such as Miami. When you brush often, a certain hairiness may appear, this can be taken away with a pilling machine/ razor. This will not have any negative influence on the durability of this textile.

With a weight of over 600 grams per linear meter, it is a great luxurious textile for both fitted and loose fitting upholstery.

Available from stock in a wide range of colours and kindly note that this elegant textile is also machine-washable at 30 degrees Celsius*.

- Dirt and damp prevention treatment applied.
- We recommend to wash the cover inside out and immediately place the cover back to the piece of furniture, slightly damp, after washing.
- Please note that during washing the damp- and dirt prevented treatment will disappear faster.

***Textaafoam originals** Established in 1970, this Dutch family business brings together craftsmen in textiles and furniture design to build an unrivalled portfolio in upholstery fabrics that meets buyer's needs every time. Featuring a wide colour range, ultimate value for money and excellent reliability in the supply chain.*

Composition

/ faceside 70%PES 30%VI
/ backside n/a
/ chenille flatweave

Suitable for

sofa's, beds, chairs with fitted and loose fitting upholstery



beige 05



blush 92



burgundy 34



cacao 83



clay 84




cream 02



darkgrey 68



ecru 102



graphite 66



indigo 90



lightgrey 60



liver 10

Please note: colours may vary according to your screen settings.



mustard 06



natural 01



pesto 194



shell 196



shitake 124



taupe 12



teal 198



wood 108



zinc 167

Please note: colours may vary according to your screen settings.

Miami - Article passport

A nice, elegant and soft quality with voluminous grip.
Available from stock in a wide range of contemporary and commercial colours.

Product characteristics

Productgroup	chenille flatweave	
Applications	sofa's, beds, chairs with fitted and loose fitting upholstery	
Composition faceside	70%PES 30%VI	
Composition backside	n/a	
Coating	needle punch	
Statistic code	58013600	
Dyeing method	piece dyed	
Available colours	21	
Packaging	bubble wrap	

Durability specifications

Test	Test specification	Executed by laboratory:	Unit	Testresult		Norm RAL GZ 430/4:2019-01		Norm DIN EN 14 465:2006-09
				Dry	Wet	DGM	DGM+	
Abrasion resistance - yarn breakage	DIN EN ISO 12947-1:2007-04, DIN EN ISO 12947-2:2017-03	CTL	cycles	85.000		min. 8.000	min. 16.000	B
Pilling	DIN EN ISO 12945-2:2000-11. 2000 cycles	CTL	grade	4		min. 3-4	min. 4	B
Colour fastness to light	DIN EN ISO 105-BO2:2014-11. Process 3, exposure level 5							
	light colours	CTL	grade	5		min. 4	min.5	B
	middle colours	CTL	grade	5		min. 4	min.5	B
	dark colours	CTL	grade	4-5		min. 4	min.5	B-C
Colour fastness to rubbing	DIN EN ISO 105-X12:2016-11							
	light colours	CTL	grade	5	5	dry: 4, wet: 3	dry: > 4, wet: 3-4	A/A
	middle colours	CTL	grade	4-5	4-5	dry: 4, wet: 3	dry: > 4, wet: 3-4	A/A
	dark colours	CTL	grade	4-5	4	dry: 4, wet: 3	dry: > 4, wet: 3-4	A/A
Ignitability (cigarette test)	 BS 5852 part 1 (1979) from The Furniture and Furnishing (Fire) (Safety) regulations: 1988 No. 1324. Schedule 4 part 1 Ignition source 0: cigarette	CTL		passed				

Processing specifications

Minimum workable width in centimeters	± 138							
Roll length in meters	± 40							
Material weight in grams per linear meter	± 616							
Test	Test specification	Executed by laboratory:	Unit	Testresult		Norm RAL GZ 430/4:2019-01		Norm DIN EN 14 465:2006-09
				Warp	Weft	DGM	DGM+	
Tensile strength	DIN EN ISO 13934-1:2013-08	CTL	Newton	861	446	min. 350	min. 400	A/B
Tear growth resistance	DIN EN ISO 13937-3:2000-06	CTL	Newton	71,6	71,6	min. 25	min. 30	A/A
Resistance to seam slippage	DIN EN ISO 13936-2:2004-07. Load 180 N	CTL	mm	2,3	2,3	max. 5	max. 4	A/A
Delamination	DIN 53530:1981-02	CTL	Newton	n/a	n/a	n/a	n/a	n/a
Chemical substances	REACH	Centexbel		passed				
	Oeko-Tex, product class II	Centexbel		certified				

Cleaning specifications

Test	Test specification	Executed by laboratory:	Unit	Testresult		Norm RAL GZ 430/4:2019-01		Norm DIN EN 14 465:2006-09
				Warp	Weft	DGM	DGM+	
Dimensional change for washing 30 degrees celcius / air drying	DIN EN ISO 5077:2008-04, DIN EN ISO 6330:2013-02, DIN EN ISO 3759:2011-08	CTL	%	-0,8	-1,6	n/a	n/a	A/A
    		- Dirt and damp prevention treatment applied. - We recommend to wash the cover inside out and immediately place the cover back to the piece of furniture, slightly damp, after washing. - Please note that during washing the damp- and dirt prevented treatment will disappear faster.						



Textaafoam b.v.
La Défense 11 | 5026 SC Tilburg
P.O. Box 12 | 5050 AA Goirle
The Netherlands

T +31(0)13 534 5934
F +31(0)13 534 7586
E info@textaafoam.nl
www.textaafoam.nl