




Renegade



**Textaafoam**  | **Comfort**  
creativity in fabrics



# Renegade

This chunky and shiny rough woven quality is in our Comfort collection, which consists only of soft, voluminous and elegant fabrics.

Our product development team wanted to develop a rough woven structure with a strong bi-colour aspect. Both are in trend again and in close cooperation with our sales team we are now proud to introduce RENEGADE. This 100% polyester flatwoven article has a very soft hand feel, due to the thick chenille yarns which are woven in this piece dyed article.

Chenille fabrics are perfect for creating cozy, warm and elegant furniture's. The light glossy yarns in warp and weft direction make this article look rich and trendy. It is suitable for tight fitted as well as loose fitting upholstery. Renegade will cheer up your furniture!

Washable 30 degrees without any problems. Now available in a wide range of contemporary colours.

- \* Please wash the cover inside out. We also recommend to put the fabric back on the furniture slightly damp after washing to ensure it dries evenly.
- \* Please note that due to chenille yarns, seat depression is possible.

*Textaafoam <sup>originals</sup> Established in 1970, this Dutch family business brings together craftsmen in textiles and furniture design to build an unrivalled portfolio in upholstery fabrics that meets buyer's needs every time. Featuring a wide colour range, ultimate value for money and excellent reliability in the supply chain.*

## Composition

/ Faceside 100%PES  
/ Chenille flatweave

## Suitable for

Sofa's, beds, chairs with fitted  
and loose fitting upholstery





pearl 106




natural 01



desert 109




shell 196




steel 149




liver 10



plumb 168




graphite 66



wood 108



teal 198



indigo 90



forest 162




copper 126



mustard 06



brandy 127



carmine 36

## Renegade - Article passport


Fabric with a multi coloured aspect, rough construction and soft and full handfeel.

Available from stock in a wide range of contemporary and commercial colours.

### Product characteristics

Productgroup	chenille flatweave	
Applications	sofa's, beds, chairs with fitted and loose fitting upholstery	
Composition faceside	100%PES	
Statistic Code	58013600	
Coating	SBR	
Dyeing method	piece dyed	
Available colours	16	










### Durability specifications

Test	Test Specification	Executed by laboratory:	Unit	Testresult		Norm RAL GZ 430/4:2016-01		Norm DIN EN 14 465:2006-09
				DRY	WET	DGM	DGM+	
Abrasion Resistance - yarn breakage	DIN EN ISO 12947-1:2007-04, DIN EN ISO 12947-2:2017-03	CTL	cycles	>100.000		min. 8.000	min. 16.000	A
Pilling	DIN EN ISO 12945-2:2000-11. 2000 cycles	CTL	grade	4		min. 3-4	min. 4	B
Colour fastness to light	DIN EN ISO 105-B02:2014-11. Process 3, exposure level 5							
	light colours	CTL	grade	5		min. 4	min. 5	A
	middle colours	CTL	grade	5		min. 4	min. 5	A
	dark colours	CTL	grade	5		min. 4	min. 5	A
Colour fastness to rubbing	DIN EN ISO 105-X12:2016-11							
	light colours	CTL	grade	5	5	dry: 4, wet: 3	dry: min 4, wet: 3-4	A/A
	middle colours	CTL	grade	4-5	5	dry: 4, wet: 3	dry: min 4, wet: 3-4	A/A
	dark colours	CTL	grade	5	5	dry: 4, wet: 3	dry: min 4, wet: 3-4	A/A
Ignatability	 BS 5852 part 1 (1979) from The Furniture and Furnishing (Fire) (Safety) Regulations: 1988 No. 1324. Schedule 4 part I. Ignition source 0: cigarette	CTL		passed				

### Processing specifications

Minimum workable width in centimeters	± 138							
Roll length in meters	± 30							
Material weight in grams per linear meter	± 714							
Test	Test Specification	Executed by laboratory:	Unit	Testresult		Norm RAL GZ 430/4:2016-01		Norm DIN EN 14 465:2006-09
				WARP	WEFT	DGM	DGM+	
Tensile strength	DIN EN ISO 13934-1:2013-08	CTL	Newton	1.157	1.897	min. 350	min. 400	A/A
Tear growth resistance	DIN EN ISO 13937-3:2000-06	CTL	Newton	140,8	170,5	min. 25	min. 30	A/A
Resistance to seam slippage	DIN EN ISO 13936-2:2004-07. Load 180 N	CTL	mm	1,8	2,0	max. 5	max. 4	A/A
Chemical substances	REACH	Centexbel		passed				

### Cleaning specifications

Test	Test Specification	Executed by laboratory:	Unit	Testresult		Norm RAL GZ 430/4:2016-01		Norm DIN EN 14 465:2006-09
				WARP	WEFT	DGM	DGM+	
Dimensional change for washing 30 degrees celcius / air drying	DIN EN ISO 5077:2008-04, DIN EN ISO 6330:2013-02, DIN EN ISO 3759:2011-08	CTL	%	+ 0,0	- 0,4	n/a	n/a	A/A
    		We recommend to immediately place the cover back to the piece of furniture slightly damp after washing.						
		   						

**Textaafoam**  
creativity in fabrics

Textaafoam b.v.  
La Défense 11 | 5026 SC Tilburg  
P.O. Box 12 | 5050 AA Goirle  
The Netherlands

T +31(0)13 534 5934  
F +31(0)13 534 7586  
E info@textaafoam.nl  
www.textaafoam.nl